# 60cm Slide-out Rangehood



### FEATURES

440m³/hr extraction, LED lighting, 2-speed settings, Concealed controls, Aluminium grease filters

 $\mathsf{MODEL/ESL60D2S}$ 

INALT?

WWW.INALTO.HOUSE

## Congratulations on your new InAlto 60cm Slide-out Rangehood!

#### INSTALLATION

Please refer to the dimensions of your rangehood shown in the diagram below.

76

9

278

When positioning the rangehood for installation and use, we advise that the rangehood is mounted at a height of between 600–750mm above the cooking surface for safety and performance of your rangehood.

Gas cooktops must have a minimum of height of 650mm from the burner to the underside of the rangehood.

Electric cooktops must have a minimum height of 600mm from the cooktop surface to the underside of the rangehood.

For a complete guide, refer to the user manual pages 12–16.



Your Slide-out Rangehood Controls

- 1 On/Off switch
- 2 Slide-out Front Fascia Rail
- 3 Rangehood housing
- 4 Inner Aluminium Grease Filter
- 5 Outer Aluminium Grease Filter
- 6 Fan Speed Switch
- 7 Light

For a complete guide on operating your rangehood refer to user manual on pages 11.

#### DETAILS

Product Size (W, D, H): 599mm × 278mm × 200mm



599

#### SUPPORT

Telephone: 1300 11 4357 Email: support@residentiagroup.com.au

MODEL/ESL60D2S

#### WWW.INALTO.HOUSE

9